



# vulcan<sup>®</sup> Kart-One

## Key performance

- High smash resistance
- Excellent half tone reproduction
- Sizes are available to suit any packaging press format
- Edge marking resistance
- Increased blanket lifetime

## MAIN APPLICATION

Packaging

**Vulcan Kart-One is available in 3-ply, 1,95 mm thickness.**



Vulcan Kart-One

## ✓ The product at a glance

<b>INK COMPATIBILITY</b>	Hybrid
<b>PRINTING SURFACE COLOUR</b>	Dark Blue
<b>THICKNESS (mm)</b>	1,95
<b>AVERAGE LOAD VALUE N/cm<sup>2</sup> @ 0,23 mm Indentation</b>	150
<b>SURFACE ROUGHNESS (Ra micron)</b>	0,6
<b>ELONGATION (%)</b>	<0,9
<b>TENSILE STRENGTHS (N/mm)</b>	>60
<b>WATER &amp; SOLVENT PROTECTION</b>	NO
<b>ADDITIONAL INFORMATION</b>	
<b>APPLICATIONS</b>	Exceptional for cardboard printing

**FOR ANY FURTHER DETAILS AND FOR A QUOTATION  
PLEASE REFER TO YOUR SALES MANAGER  
OR EMAIL US AT: [printing@trelleborg.com](mailto:printing@trelleborg.com)**