

Rollin® Type150

Key performance

- Consistent throw length, uniform nip pressure, easy washup
- The best adhesive in the market to avoid creeping and lifting
- Clean and easy removal from the cylinder
- Improved blanket lifetime

MAIN APPLICATION

Business Forms, labels

Rollin Type150 available in multiple ply type and multiple thickness.



Rollin Type150

✓ The product at a glance

INK COMPATIBILITY	UV
PRINTING SURFACE COLOUR	Light Blue
THICKNESS (mm)	Buffed surface: Type 150 M: 0,90 /Type 150 S: 0,94 /Type 150 R: 0,98 / Type 150 RT: 1,00 / Type 150 RTA: 1.04 mm/ Type 150 RTA / HÉLIOS: 1.07 mm +/- 0.01
AVERAGE LOAD VALUE N/cm² @ 0,23 mm Indentation	250
SURFACE ROUGHNESS (Ra micron)	1,2/2,2
ELONGATION (%)	NA
TENSILE STRENGTHS (N/mm)	NA
WATER & SOLVENT PROTECTION	No

**FOR ANY FURTHER DETAILS AND FOR A QUOTATION
PLEASE REFER TO YOUR SALES MANAGER
OR EMAIL US AT: printing@trelleborg.com**