

ROSSA H.P. HIGH PERFORMANCE

TYREF ROSSA H.P.

High performance coating plate for offset coating.

Available in thicknesses:

- 1.15mm (0.045")
- 1.35mm (0.053")
- 1.95mm (0.077")

Available widths:

- 1080mm (42^{1/2}"
- 1320mm (52")
- 1480mm (58^{1/4}"
- 1580mm (62^{1/4}"

The Rossa H.P. surface was developed to optimise the transfer and performance when applying speciality coatings including Soft Touch, Drip Off, Satin and Matt products.

The soft smooth surface allows these coatings to be applied with minimum pressure giving superior transfer and lay.

The new construction gives the product additional stability on press and easy stripping characteristics.



Surface	Rubber
Thickness	1.15mm; 1.35mm; 1.95mm - 0.045"; 0.053"; 0.077"
Relief depth	0.80mm; 1.00mm; 1.60mm - 0.031"; 0.040"; 0.063"
Hardness	58° Shore A
Colour	Red
Application	Water based and UV coating

PRODUCT FEATURES

- Suitable for speciality water based (aqueous) and UV coating applications
- Abrasive resistant surface
- Solvent resistant construction
- Excellent coating lay and transfer
- Superior sheet release
- No ink build up characteristics
- Durable, long life
- Consistent gauge tolerance
- Easy, consistent cutting and peeling
- Suitable for cutting manually or by plotter